

PRODUCT DATA SHEET

INTERIOR PLASTER

Description	INTERIOR PLASTER is specially formulated from inorganic material for smoothening of masonry surfaces with high build thickness without film cracking.
Uses	INTERIOR PLASTER is used as putty to treat the unevenness for ceiling and masonry substrate.
Finish	Matt/ Grey
Features	- Very tough and durable - Easy to use - Excellent adhesion of recommended substrates - No cracking tendency under normal application up to 6 mm per application - Better water resistance
APPLICATION DATA	
Surface Preparation	Surface should be clean, dry and stable before application. - Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter below 60% by Lutron MS-7003 Moisture meter Extremely dry and absorbent substrates should be moistened with water before applying INTERIOR PLASTER.
Application Methods	Use trowel or airless spraying to apply INTERIOR PLASTER on the surface with thickness up to 6 mm depend on the surface per application.
Paint Consumption	Theoretical: 20.0 – 25.0 m ² /bag (40Kg) depend on thickness applied
Mixing Instruction	Mix 01 bag INTERIOR PLASTER with 10 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes). Add powder to water to avoid lumpiness. Allow the mixture to stand for about 10 minutes then mix again until homogenous. Ready plaster should be used in 2 hours after mixing.
Cleaning	Wash all equipment immediately after use with clean water
Storage	INTERIOR PLASTER is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
Packing	40 Kgs/Bag

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

INTERIOR PLASTER

Precaution	Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc. The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc. Do not use INTERIOR PLASTER on unstable painted surfaces, water soluble plasters or smoothing floors. Do not apply INTERIOR PLASTER when the temperature is below 10°C & moisture is over 85%.
NOTE	<i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i>

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com