



INSTRUCTIONS FOR USE

Product code: **W-102 Waterborne roller-applied primer**

Product description and applications:

This one-component water-based primer is designed for roller application. It features high transparency, good oil absorption, excellent filling properties, strong adhesion, and fast drying. The product is suitable for use as a primer coat for roller-applied finishes on flat surfaces.

Product characteristics:

- High transparency
- Excellent adhesion
- Excellent roller application performance
- Good filling and build-up properties

Basic data:

Item	Specification
Appearance	Milky white to semi-transparent liquid
Solid content	35 ± 2%
Viscosity (30°C)	75±5KU

Application data:

Application method	Roller
Thinner	Purified water, usually no additives required
Application conditions	10~35°C/65~85%RH
Recommended film thickness	120 µm wet film

Precautions:

1. Stir thoroughly before adding water to achieve the desired viscosity.
2. Before applying the primer, ensure the surface is smoothly sanded with 600# sandpaper.
3. Seal any unused paint immediately after use.

Tool cleaning:

After use, clean spray guns and all tools/equipment immediately with thinner or spray gun cleaning solution to prevent drying. Dispose of waste liquid generated during cleaning in accordance with applicable regulations.

Safety precautions:

This product is intended for industrial use only and should be handled by trained personnel. During any coating process, the following precautions must be observed:

- Wear appropriate protective gloves, respirators, safety goggles, and protective clothing.
- Avoid contact with skin and eyes. In case of skin contact, wash thoroughly with warm water and/or suitable detergent. If paint gets into the eyes, rinse immediately with plenty of water



Environmental Application Solution Supplier
Nhà cung cấp dịch vụ giải pháp sơn phủ thân thiện với môi trường

and seek medical attention.

- Ensure adequate ventilation in the working area.
- Avoid inhalation of paint fumes under all circumstances.

Packaging specification : 20KG

Storage:

Storage temperature:	5~35°C
Shelf life:	12 months. Store in a cool, dry place, away from heat sources and open flames

Disclaimer:

The information provided in this instruction sheet is the most comprehensive and accurate data currently available from our company. However, since the conditions of product use are beyond our control, this information does not constitute any form of warranty and is intended solely to assist customers in selecting suitable products. Due to ongoing product development and changes in company policies, all information contained herein should be confirmed with us prior to use.