



## INSTRUCTIONS FOR USE

**Product code:** VW-201 Water-based white primer

### Product description and applications:

This one-component water-based white electrostatic spray primer has excellent coverage, outstanding electrostatic spray adhesion, and fast drying performance. It is suitable for use as a primer coat for electrostatically sprayed colored coating systems.

### Product characteristics:

- High coverage
- Excellent adhesion
- Outstanding coating absorption performance
- Fast drying and good anti-caking performance

### Basic data:

Item	Specification
Appearance	White viscous liquid
Solid content	55 ± 2%
Viscosity (30°C)	90±10KU

### Application data:

Application method	<b>Electrostatic spray</b>
Thinner	Purified water
Application conditions	10~35°C/65~85%RH
Recommended film thickness	80 µm wet film
Viscosity (30°C)	20–50 seconds

### Precautions:

1. Stir thoroughly before adding water to achieve the desired viscosity.
2. Before applying the primer, ensure the surface is smoothly sanded with 600# sandpaper.
3. Seal any unused paint immediately after use.

### Tool cleaning:

After use, clean spray guns and all tools/equipment immediately with thinner or spray gun cleaning solution to prevent drying. Dispose of waste liquid generated during cleaning in accordance with applicable regulations.

### Safety precautions:

This product is intended for industrial use only and should be handled by trained personnel. During any coating process, the following precautions must be observed:

- Wear appropriate protective gloves, respirators, safety goggles, and protective clothing.
- Avoid contact with skin and eyes. In case of skin contact, wash thoroughly with warm



*Environmental Application Solution Supplier*  
**à cung cấp dịch vụ giải pháp sơn phủ thân thiện với môi trường**

---

water and/or suitable detergent. If paint gets into the eyes, rinse immediately with plenty of water and seek medical attention.

- Ensure adequate ventilation in the working area.
- Avoid inhalation of paint fumes under all circumstances.

**Packaging specification:** 20KG

**Storage:**

---

Storage temperature:	5~35°C
Shelf life:	12 months. Store in a cool, dry place, away from heat sources and open flames

---

**Disclaimer:**

The information provided in this instruction sheet is the most comprehensive and accurate data currently available from our company. However, since the conditions of product use are beyond our control, this information does not constitute any form of warranty and is intended solely to assist customers in selecting suitable products. Due to ongoing product development and changes in company policies, all information contained herein should be confirmed with us prior to use.